

MINE SUPPLY INTERNATIONAL

MANUFACTURERS REPRESENTATIVES - INTERNATIONAL MARKETS

CABLE SADDLE



Cable Saddle

- ✓ Used for hoisting and supporting cables in various applications
- ✓ Tightens its grip as the cable is being hoisted
- ✓ Designed to meet the minimum bending radius of the cable
- ✓ Prevents cable damage to improper handling
- ✓ Non-Skid internal surface to retain cable
- ✓ Sling is constructed of two-ply latex treated webbing
- ✓ Lightweight, easy handling
- ✓ Highly visible
- ✓ Strong, hard wearing and flexible polyurethane
- ✓ High and Low temperature resistant
- ✓ In use around the world in extreme mining operations
- ✓ Use when cable support is critical

Cable Diameter		Weight		Length		Choker Capacity		MineSupply Catalogue Number	Replacement Sling Catalogue Number
(mm)	(in)	(kg)	(lb)	(mm)	(in)	(kg)	(lb)		
49 - 54	1.93 - 2.12	3.97	8.75	540	21.25	2041	4500	CS . 101	CRS . 101
55 - 64	2.16 - 2.51	4.42	9.75	540	21.25	2041	4500	CS . 102	CRS . 102
65 - 69	2.55 - 2.71	4.76	10.50	540	21.25	2041	4500	CS . 103	CRS . 103
70 - 79	2.75 - 3.11	5.10	11.25	540	21.25	2041	4500	CS . 104	CRS . 104
80 - 89	3.14 - 3.50	5.44	12.00	540	21.25	2041	4500	CS . 105	CRS . 105
90 - 99	3.54 - 3.89	5.78	12.75	540	21.25	2041	4500	CS . 106	CRS . 106
100 - 109	3.93 - 4.29	6.80	15.00	540	21.25	3447	7600	CS . 107	CRS . 107
110 - 120	4.33 - 4.69	7.16	16.00	540	21.25	3447	7600	CS . 108	CRS . 108